



Multi-Hazard Suppression Control Panel



NEW

Features

- This compact and esthetic unit is ideally suited for variety of agent releasing applications such as FM-200, CO2, Dry & Wet Chemical.
- Expansion is available in order to protect more areas.
- Auto and Manual operation for agent releasing.
- System enables highly reliable monitoring and suppression control for up to eight separate hazards.
- Audible and visible indication when system has fault condition.
- Digital Release Countdown.

Optional Features

- 24 Characters LCD Display with 255 Event History Log.
- Printer (built into front door)
- Single-tone Voice PA System.
- Multi-tone Voice PA System.
- Special case design includes agent tank with control unit.

Specification

Model	AH-02120
Supply Voltage	110 / 220 VAC 50 / 60Hz
Standby Voltage	24 VDC 4Ah
Loop Voltage	24 VDC
Detector Per Loop	Up to 30 detectors
EOL Resistance	10kΩ
Detection Type	Cross-zone detection
Dimensions	520mm (H) x 390mm (W) x 135mm (D) 1000mm (H) x 500mm (W) x 175mm (D)
Color	Ivory

Effective Alert Area

Electromagnetic Valve	24 VDC
Sounder	24 VDC 200mA
Releasing Indicator	24 VDC 200mA
Manual Pull Station	Up to 10 / zone via RS 485
Speaker	12 VDC (3W 8Ω / zone)