

**roger**<sup>®</sup>

# PRT 12 Domino Series Outdoor Access Terminal



CE

ROGER ACCESS CONTROL SYSTEM



RACS

**roger**<sup>®</sup>  
PRT 12-BK



PRT 12

CE

#### Ordering information

PRT12	RFID/PIN version, ONLINE/OFFLINE operation
PRT12-BK	RFID only version, ONLINE/OFFLINE operation
AT89ISP	Firmware downloading cable

#### Technical specification

Operating voltage range	10...16VDC
Current consumption	avg. 60mA
Tamper	an open collector transistor output, 20mA max. sink current
Communication standard (ONLINE mode)	Wiegand26/34/42/64bit, Magstripe or RACS (Roger)
Cards	UNIQUE type, EM4100/4102 compatible
Ingress protection	IP65
Environmental class	Class IV – Outdoor General, temp. -25°C...+60°C
Dimensions	46 X 150.5 X 23 mm
Weight	~ 150g

## PRT 12 Domino Series Outdoor Access Terminal

*Note: The product descriptions in this document refer to device's firmware version 71.0 or higher.*

#### Features:

- UNIQUE (EM4100/4102) tags
- up to 12cm reading range
- TAMPER output
- general outdoor environment
- CE mark

#### ONLINE Mode

- Wiegand 26/34/42/66 bit interface
- Magstripe (ABA Track II emulation) interface
- RACS (Roger) interface
- LED/Buzzer control input

#### OFFLINE Mode

- 120 cards and PINs
- user indexing
- Card, PIN or Card+PIN identification
- Door Contact and Exit Button inputs
- Alarm and Door Bell outputs
- integration with Intruder Alarm System through I/Os
- Entry/Exit control (requires second PRT series reader)
- utilizes built-in or remote (on XM-2 expander) I/Os
- manual programming

**roger**<sup>®</sup>



*All content, specifications and availability subject to change without prior notice*