

# ROGER FR702

## Standalone Fingerprint Reader

### MAIN FEATURES

- silicon keypad
- LCD display
- events recording
- identification mode: 1:1 or 1:N
- user indexing
- holiday management
- operating modes: **online** (as a Wiegand reader connected to access controller), **offline** (as a standalone controller)

### OFFLINE MODE FEATURES:

- 1500 users (finger templates)
- 30 000 events buffer
- 50 time schedules
- 5 groups
- configuration trough TCP/IP, RS485 or RS232

### ONLINE MODE FEATURES:

- 1500 users (finger templates)
- Wiegand 26 bit data output format
- direct management from RACS software

**ROGER** (Made In Poland)



<b>Operating voltage</b>	12 VDC
<b>Power consumption</b>	stand-by current: 50mA, operational current: 400mA
<b>Relay output</b>	3A/12VDC
<b>Communication</b>	TCP/IP, RS232 or RS485
<b>Identification time</b>	max. 2 seconds
<b>FRR (False Reject Rate)</b>	max. 1%
<b>FAR (False Accept Rate)</b>	max. 0.0001%
<b>Operating temperature</b>	0°C...45°C
<b>Operating humidity</b>	20-80%
<b>Dimensions (W X D X H)</b>	82 X 35 X 180 mm

►Design and specifications are subject to change without notice.

Authorized System Integrator